

IN THE CLAIMS

Please amend claims 1- 4 and 7, cancel claims 5, 6, and 8-32, and add new claims 33 and 34 as follows:

- B1  
Cont
1. (Currently Amended) An image pickup apparatus comprising:
- a plurality of pixels each including a photoelectric conversion ~~means for converting~~ portion which converts an optical signal from an object into an electrical signal and a read ~~means for reading~~ portion which reads out the signal from said photoelectric conversion ~~means~~ portion to an output line;
- ~~difference means for performing difference processing on a noise component contained in the signal read by said read means;~~
- a drive control portion which controls a first mode for reading out from said read portion a pixel noise signal which is obtained by resetting an input portion of said read portion, and a second mode for reading out from said read portion an image signal which includes a signal generated by said photoelectric conversion portion;
- a correction portion which subjects the image signal read out from said read portion, to correction processing which uses the pixel noise signal;
- a detection ~~means for detecting an image pickup~~ portion which detects an object condition; and
- ~~correction means for performing correction of execution of difference processing in accordance with an output from said detection means~~
- a switching portion which switches over the correction processing

of said correction portion in accordance with an output of said detection portion.

B1  
vent

2. (Currently Amended) An apparatus according to claim 1, wherein said detection ~~means~~ portion detects that a signal level of ~~[[a]]~~ the image signal ~~generated by said photoelectric conversion means~~ is higher than a predetermined value.

3. (Currently Amended) An apparatus according to claim 1, wherein said detection ~~means~~ portion detects that a signal level of the pixel noise signal ~~generated in each pixel~~ is higher than a predetermined value.

4. (Currently Amended) An apparatus according to claim 1, wherein said ~~correction means controls said difference means not to perform difference operation~~ switching portion effects switching-over in accordance with the output of said detection portion so as not to perform the correction processing.

5.- 6. (Cancelled)

7. (Currently Amended) An apparatus according to claim 1, wherein said ~~correction means~~ switching portion replaces a signal output from said ~~difference means~~ correction portion with a signal of a predetermined signal level in accordance with the output of said detection portion.

8.-32. (Cancelled)

B1  
Amend

33. (New) An image pickup system comprising:  
said image pickup apparatus as defined in claim 1;  
a color correction portion which performs color correction on a signal  
output from said image pickup apparatus; and  
a control portion which controls said image pickup apparatus and said  
color correction portion.

34. (New) An image pickup system comprising:  
said image pickup apparatus defined in claim 1;  
an LED array for irradiating said image pickup apparatus with light; and  
an original feeding portion which feeds an original.

---